

Design for Living by Enviro

Kodiak Wood Stoves
by Enviro



The KODIAK - Enviro's Freestanding Wood Stove



The Kodiak

1200 flat top and step top 1700 flat top and step top 2100 step top

Flue diameter	6"	6"	6"
Steel thickness of top	5/16" / 1/4"	5/16" / 1/4"	1/4"
Firebox Capacity	1.85 cu ft.	2.50 cu ft.	3.10 cu ft.
Heating Area *	800-1500 sq ft.	1000-2200 sq ft.	1200-2500 sq ft.
Burn times *	6 -10 hours	8 - 12 hours	8 -12 hours
Seasoned Cord Wood Output BTU's*	67,000 BTU's	74,000 BTU's	82,000 BTU's
Efficiency*	72 %	75%	75%
Weight	400 lbs.	450 lbs.	500 lbs.
EPA Emissions	3.3 g per hour	4.5 g per hour	2.9 g per hour
Mobile Home Approved	Yes	Yes	No
Maximum Log Size	18"	20"	22 1/2"

Dimensions

1	22 1/2"	27"	30"
2	6"	6"	6"
3	16 1/2"	21"	24"
4	18 1/4"	23"	26 3/4"
5	25"	25"	25"
6 - flat top	30 1/4"	30 1/4"	-
6 - step top	32 3/4"	32 3/4"	33 3/4"
7 - flat top	28 1/4"	28 1/4"	-
7 - step top	31 1/4"	31 1/4"	32 1/4"
8	10"	10"	10"
9	24 3/8"	24 3/8"	22"



Brushed Nickel, Nickel, 24 kt. Gold and Painted Options

Featuring "Progressive Burn Technology"

Progressive Burn Technology is designed to keep hot embers in the firebox after a nights burning. We do this by restricting the air in the back of the firebox (leaving hot embers for you to start your morning fire!) Our secondary air tubes then add more air to the fire as the burn progresses to the front. This maintains efficiencies and keeps emissions low.

The Enviro Kodiak wood stove, like the Kodiak bear, is robust and superior.

Exclusive features to Enviro wood stove:

- radiant and convective heat to maximize the heat output
- large firebox capacity for long overnight burns
- single, easy-to-use air control adjusts the heat output and regulates the fire
- twin pilot-injection ports tuned to deliver fast starts*
- ultra strong air wash helps to keep the glass clean
- up to 5/16" thick steel construction*
- 1/2" diameter hinges and door handle
- long life ceramic top baffle
- 3 or 4 X 1" 304 grade stainless steel secondary air tubes*
- optional 130 cfm variable speed fan is available for all models

* apply to 1200/1700 models only

**Clearance to Combustibles					
	1200		1700		2100
	Single Wall Pipe	Double Wall Pipe	Single Wall Pipe	Double Wall Pipe	Single Wall Pipe
A	13"	13"	20"	13"	22"
B	11"	10"	12"	10"	12"
C	9"	8"	10"	8 1/2"	8"
D	22"	22"	29"	22"	31"
E	14"	13"	15"	13"	16 1/2"
F	17.5"	16.5"	18.5"	17"	
G	16" (18" CDN)	16" (18" CDN)	16" (18" CDN)	16" (18" CDN)	16" (18" CDN)
H	6" (8" CDN)	6" (8" CDN)	6" (8" CDN)	6" (8" CDN)	6" (8" CDN)

** Figures will vary with heat shield (see owner's manual)



2100

**- The Enviro Kodiak -
Strong, Efficient, Clean Burning.**

Authorized Dealer



Manufactured by Sherwood Industries Ltd., Victoria, BC Canada • www.envirofire.biz • email: enviro@shaw.ca

*Figures will vary considerably with floor plan, house layout and heat loss of house. Due to on-going product development, product appearances and specifications are subject to change without notice. Efficiency and area heated will vary according to location and fuel. Approved for sale in Canada and the United States. Printed in Canada, June 2006.